



## Industrial Rubber Inc.

3609 S. High Oklahoma City, Oklahoma 73129  
Phone 405/632-9783 Fax 405/634-9637

### ***Industrial Rubber, Inc. Wooden Cementing Plugs***

Industrial Rubber's Wooden Cementing Plugs  
are designed for *rugged dependability*.

These plugs are constructed from High Grade wood and Specially  
Compounded Rubber.

***Three*** core designs are used for  
top plugs.



A **solid** core is used for casing sizes from 4  
1/2" to 6 5/8".



A **pinwheel** design is employed for casing sizes 7" through 13 3/8".



An **octagonal** core design with solid wooden hub and eight spokes is used for the 16" and 20" casing.

**Weight is approximate and will vary.**

<b>Wooden Cementing Plugs Specifications</b>			
<u>Casing Size</u>	<u>Plugs O.D.</u>	<u>Plug Length</u>	<u>Plug Weight</u>
4 1/2"	4 1/4"	8 1/2"	2 lbs.
5 1/2"	5"	8 1/2"	2 1/2 lbs.
6 5/8"	6 1/4"	8 3/4"	4 lbs.
7"	6 1/2"	8 3/4"	4 1/4 lbs.
7 5/8"	7 1/4"	8 3/4"	5 1/4 lbs.
8 5/8"	8 1/4"	9 3/4"	6 1/4 lbs.
9 5/8"	9"	9 3/4"	7 1/2 lbs.
10 3/4"	10 1/4"	10 3/4"	8 lbs.
11 3/4"	11 1/4"	11 3/4"	13 lbs.
12 3/4"	12 1/4"	12 3/4"	15 lbs.
13 3/8"	12 3/4"	13 1/4"	15 lbs.
16"	16"	16 1/2"	35 lbs.
18 5/8"	18 1/4"	18 1/2"	28 lbs.
20"	19 3/4"	20 1/2"	63 lbs.

<b>Top Wooden Cementing Plugs</b>	
<u>Size</u>	<u>Part Number</u>
4 1/2"	120-0044
5 1/2"	120-0054
6 5/8"	120-0065
7"	120-0070
7 5/8"	120-0075
8 5/8"	120-0085
9 5/8"	120-0095
10 3/4"	120-0106
11 3/4"	120-0116
12 3/4"	120-0126
13 3/8"	120-0133
16"	120-0160
18 5/8"	120-0185
20"	120-0200